

UA2 Thin Client

Redefining the office Workspace



Ready



"Say goodbye to clutter and hello to simplicity with the UA2—Designed for industries that demand precision and style, such as finance, healthcare, and retail."



Power in the Palm of Your Hand

UA2's palm-sized design delivers robust office solutions, enabling Unified Communication for seamless calls, meetings, and messaging—all within your grasp



Big on Savings, Small on Energy

Powered by the Intel Alder Lake, UA2's fanless design consumes just 7 watts per hour—8x more efficient than traditional PCs



One Cable, Endless Possibilities

Multitask effortlessly, even in tight spaces. UA2 simplifies your workspace with a single USB Type-C cable, handling data storage, power delivery, audio, and video



Work Clean, Work Efficiently

Designed for industries that require clutter-free environments, such as finance, healthcare, and retail sectors. Enjoy a organized workspace without sacrificing top-tier performance

UA2 Thin Client

Redefining the office Workspace



Performance

CPU	Intel® Alder Lake N100 processor supports up to 3.4GHz max turbo frequency, Quad-Core
Memory	8GB DDR4-3200MHz, Single-channel (Up to 16GB optional)
Multiple Display	2 DP 1.4 and 1 USB-C DP Alt mode - Up to 1 x 4K60 + 2 x 1080P concurrent - Up to 2 x 4K60 HDR
Display Resolution	4K 60Hz (Max)
Graphic & Multimedia	Intel® 12th UHD Graphics 24EUs

Security / Manageability

Processor Security	Intel® boot guard
Security Lock	Security lock 3*7mm
WoL	RJ45 LAN with standby power design supports Magic Packet wake-up event
TPM	Infineon TPM 2.0

Expandability

WiFi (Optional)	- Intel AX210 802.11 a/b/g/n/ac/ax 2 external antenna holes reserved - Bluetooth 5.4
Storage	- Onboard 32GB eMMC as default (Up to 64GB optional) - mSATA slot for SSD installation
LAN	RJ-45 10/100/1000Mbps
USB	4 USB-A 2.0, 2 USB-A 3.2 Gen1, 1 USB-C 3.2 Gen2 with DP Alt Mode, power delivery, data storage
Power	DC 12V/ 4A 48W power adapter
Audio & Sound	Combo audio jack for headset & internal speaker

Environment

Cooling	Passive cooling (Noise-Free)
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F in vertical position
Operating Humidity	20% - 80% non-condensing
Certificates	CE, TÜV-GS, Energy Star 9.0, WEEE, EPEAT Bronze

Physical

Dimension (w x h x d) & Weight	37 x 186 x 157mm (without foot stand) / 0.9Kg 57 x 191.5 x 157mm (with foot stand) / 0.94Kg
---	---

Note: UltrArmor reserves the right to modify specifications without notice.